



CAT 6 UTP PATCH CABLE

105-6000/6100/6200/6300/6500/6600

Phone +33 75 864 2169

Email info@angnetworks.com

Log 202, 5rue Albert Thomas, 38100 Grenoble, France.



Industry Standards

- ISO/IEC 11801-1, TIA-568.2-D
- EN 50173-1, EN 50288-6
- IEC 61935-2, IEC 60794-2
- IEC 61156-5, IEC 60322-1-2
- ETL Verified AS/CA S008:2020

Applications

- 1000BASE-TX Gigabit Ethernet
- 1000BASE-T Gigabit Ethernet
- 100BASE-TX Fast Ethernet
- 10BASE-T Ethernet
- Voice, Video, and other applications

Overview

- Constructed from high-quality four-pair 24 AWG stranded copper wire
- Available in various colors and lengths
- Pre-terminated with RJ45 plugs
- Features anti-snap slim strain relief slip-on boots

Ordering Information

Part No	Description	Color	Part No	Description	Color	Part No	Description	Color
105-6000_1	CAT.6 0.5M PATCH CORD	GRAY	105-6200_1	CAT.6 2M PATCH CORD	GRAY	105-6500_1	CAT.6 5M PATCH CORD	GRAY
105-6000_2	CAT.6 0.5M PATCH CORD	BLUE	105-6200_2	CAT.6 2M PATCH CORD	BLUE	105-6500_2	CAT.6 5M PATCH CORD	BLUE
105-6000_3	CAT.6 0.5M PATCH CORD	GREEN	105-6200_3	CAT.6 2M PATCH CORD	GREEN	105-6500_3	CAT.6 5M PATCH CORD	GREEN
105-6000_4	CAT.6 0.5M PATCH CORD	YELLOW	105-6200_4	CAT.6 2M PATCH CORD	YELLOW	105-6500_4	CAT.6 5M PATCH CORD	YELLOW
105-6000_5	CAT.6 0.5M PATCH CORD	RED	105-6200_5	CAT.6 2M PATCH CORD	RED	105-6500_5	CAT.6 5M PATCH CORD	RED
105-6000_6	CAT.6 0.5M PATCH CORD	BLACK	105-6200_6	CAT.6 2M PATCH CORD	BLACK	105-6500_6	CAT.6 5M PATCH CORD	BLACK
105-6000_7	CAT.6 0.5M PATCH CORD	ORANGE	105-6200_7	CAT.6 2M PATCH CORD	ORANGE	105-6500_7	CAT.6 5M PATCH CORD	ORANGE
105-6100_1	CAT.6 1M PATCH CORD	GRAY	105-6300_1	CAT.6 3M PATCH CORD	GRAY	105-6600_1	CAT.6 10M PATCH CORD	GRAY
105-6100_2	CAT.6 1M PATCH CORD	BLUE	105-6300_2	CAT.6 3M PATCH CORD	BLUE	105-6600_2	CAT.6 10M PATCH CORD	BLUE
105-6100_3	CAT.6 1M PATCH CORD	GREEN	105-6300_3	CAT.6 3M PATCH CORD	GREEN	105-6600_3	CAT.6 10M PATCH CORD	GREEN
105-6100_4	CAT.6 1M PATCH CORD	YELLOW	105-6300_4	CAT.6 3M PATCH CORD	YELLOW	105-6600_4	CAT.6 10M PATCH CORD	YELLOW
105-6100_5	CAT.6 1M PATCH CORD	RED	105-6300_5	CAT.6 3M PATCH CORD	RED	105-6600_5	CAT.6 10M PATCH CORD	RED
105-6100_6	CAT.6 1M PATCH CORD	BLACK	105-6300_6	CAT.6 3M PATCH CORD	BLACK	105-6600_6	CAT.6 10M PATCH CORD	BLACK
105-6100_7	CAT.6 1M PATCH CORD	ORANGE	105-6300_7	CAT.6 3M PATCH CORD	ORANGE	105-6600_7	CAT.6 10M PATCH CORD	ORANGE

PRODUCT TECHNICAL SPECIFICATION | CAT 6 UTP PATCH CABLE

Product Electrical Characteristics:

- Conductor size: 24 AWG stranded copper wire
- Plug minimum operating life: 750 insertion cycles
- RJ45 plug and boot material: Clear polycarbonate
- Material thickness: 0.35mm thick copper alloy
- Contact plating: Selective gold

Sheath Physical Properties:

- Sheath material: PVC
- Nominal outer diameter (O.D.): 5.9mm
- Bend radius: 4 times the O.D.
- Operating temperature range: -20°C to +70°C

HEADQUARTERS



A&G Technologies CO., Limited,
Log 202, 5rue Albert Thomas, 38100
Grenoble, France.

+33 75 864 2169

REGIONAL OFFICE



A&G Technologies (HK) CO., Limited,
Room 803, Chevalier House, 45-51 Chatham Road
South, Tsim Sha Tsui, Kowloon, Hong Kong.

+852 5420 8788

CONNECT THE FUTURE



info@angnetworks.com



www.angnetworks.com

© 2025 A&G Technologies. All Rights Reserved.