


CAT 5e UTP CABLE

108-51001

Phone
+33 75 864 2169

Email
info@angnetworks.com

Log 202, 5rue Albert Thomas, 38100
Grenoble, France.



Overview

- CAT. 5e UTP Cable designed for Ethernet networking applications.
- Suitable for indoor network installations.
- Sheath Printing: A&G CAT.5e U/UTP SOLID 24AWG×4P CM (UL) E525067 AG01 ETL VERIFIED to ANSI/TIA-568.2-D 0001M.....0305 (Month /Year).
- Category: U/UTP CAT5E-4P-PVC-CM.
Ideal for ResidentialNetworking, Commercial Networking and Industrial Networking.

Industry Standard

- ISO/IEC11801
- TIA-568.2-D

Applications



- 100BASE –T Ethernet (IEEE 802.3)
- 10BASE –T (IEEE 802.3)
- 16Mbps Token Ring (IEEE 802.5)
- 100VG- AnyLAN (IEEE 802. 12)
- Voice; T1; ISDN
- 155/622Mbps ATM
- 1000Mbps Gigabit Ethernet
- 550MHz Broadband Video

Ordering Information

Part Number	Description
108-51001	CAT. 5e UTP CABLE 305M BOX

General Information

- Conductor: Solid Bare Copper, 24AWG × 4 pairs
- Insulation: High-Density Polyethylene (HDPE)
- Sheath: PVC (Polyvinyl Chloride), RoHS compliant
- Sheath Thickness: 0.50 ± 0.05 mm
- External Diameter: 5.0 ± 0.4 mm
- Core Color Coding:
 - White-Blue/Blue
 - White-Orange/Orange
 - White-Green/Green
 - White-Brown/Brown
- Packaging: 305-meter box
- Rip-cord: Yes
- Drain Wire: No



PRODUCT TECHNICAL SPECIFICATION | CAT 5e UTP CABLE

Product Electrical Characteristics:

- 1.0-100.0MHz Impedance(Ω): 100 $\pm$ 15
- 1.0-100.0MHz Delay Skew (ns/100m): $\leq$ 45
- DC Resistance(Ω /100m) max: 9.5
- DC Conductor Resistance Unbalance (%) max: 5.0

Sheath Physical Properties:

- Before Aging: Tensile Strength (Mpa) $\geq$ 13.5, Elongation (%) $\geq$ 150
- After Aging (100°Cx24hx7d): Tensile Strength (Mpa) $\geq$ 12.5, Elongation (%) $\geq$ 125
- Cold bend (-20 $\pm$ 2°Cx4h): 8xCable O.D. No visible cracks
- Installation Temperature: 0°C to +50°C
- Operating Temperature: -20°C to +60°C

Technical Performance (100m)

Frequency (MHz)	RL ($\geq$ dB)	Attenuation ($\leq$ dB)	NEXT ($\geq$ dB)	Delay ($\leq$ ns)
1.0	20.0	2.0	65.3	570.00
4.0	23.0	4.1	56.3	552.00
8.0	24.5	5.8	51.8	546.73
10.0	25.0	6.5	50.3	545.38
16.0	25.0	8.2	47.2	543.00
20.0	25.0	9.3	45.8	542.05
25.0	24.3	10.4	44.3	541.20
31.25	23.6	11.7	42.9	540.44
62.5	21.5	17.0	38.4	538.55
100	20.1	22.0	35.3	537.60

Frequency (MHz)	PSNEXT (db) $\geq$	ELFEXT (dB) $\geq$	PSELFEXT (dB) $\geq$
1.0	62.3	63.8	60.8
4.0	53.3	51.8	48.8
8.0	48.8	45.7	42.7
10.0	47.3	43.8	40.8
16.0	44.4	39.7	36.7
20.0	42.8	37.8	34.8
25.0	41.3	35.8	32.8
31.25	39.9	33.9	30.9
62.5	35.4	27.9	24.9
100	32.3	23.8	20.8