



CAT 6A S/FTP LSZH PATCH CORD

105-9X001

Phone
+33 75 864 2169

Email
info@angnetworks.com

Log 202, 5rue Albert Thomas, 38100
Grenoble, France.



Overview

- Category: S/FTP-CAT6A-4P-LSZH
- Pre-terminated with RJ45 plugs.
- Construction Type: S/FTP (Shielded and Foiled Twisted Pair)
- Foil Material: Aluminum Mylar (Aluminum inward) per pair

Ordering Information

Part Number	Description
105-91001	CAT.6A 1M PATCH CORD
105-92001	CAT.6A 2M PATCH CORD
105-93001	CAT.6A 3M PATCH CORD
105-95001	CAT.6A 5M PATCH CORD

Industry Standard

- ISO/IEC 11801
- EN 50339, EN 60332-1-2
- TIA/EIA-568C.0
- ANSI/TIA 1096-A
- IEC 61156, IEC 61034
- IEC 60332-1-2, IEC 607454

Applications

- Bandwith 500MHz
- 10GBASE-T Ethernet / 10BASE-TX Ethernet
- 100BASE-TX Fast Ethernet
- 1000BASE-TX Gigabit Ethernet
- 1000BASE-T Gigabit Ethernet

General Information

- Conductor Material: Solid Bare Copper
- Conductor Wire Size: 26 AWG
- Insulation Material: Sjin-Foam-Skin PE
- Insulation Diameter: 1.330±0.05mm
- Sheath Material: LSZH (Low Smoke Zero Halogen), compiles with RoHS
- Core Color:
 1. White-Blue/Blue
 2. White-Orange/Orange
 3. White-Green/Green
 4. White-Brown/Brown

PRODUCT TECHNICAL SPECIFICATION | CAT 6A S/FTP LSZH PATCH CORD

Product Electrical Characteristics:

- Impedance: 15Ω/100m at 20°C
- DC Insulation Resistance: 1500MΩ/100m min.
- D.C.Resistance (Max.): 14.8 Ω /100m at 20°C

Sheath Physical Properties:

- Operation Temperature: -20°C to +70°C
- Storage Temperature: -20°C to +70°C

HEADQUARTERS



A&G Technologies CO., Limited,
Log 202, 5rue Albert Thomas, 38100
Grenoble, France.

+33 75 864 2169

REGIONAL OFFICE



A&G Technologies (HK) CO., Limited,
Room 803, Chevalier House, 45-51 Chatham Road
South, Tsim Sha Tsui, Kowloon, Hong Kong.

+852 5420 8788

CONNECT THE FUTURE



info@angnetworks.com



www.angnetworks.com