


SC PIGTAIL 50/125 MM OM3

119-01131

Phone
+33 75 864 2169

Email
info@angnetworks.com

Log 202, 5rue Albert Thomas, 38100
Grenoble, France.



Overview

- Fiber Type: Multi Mode (50/125 um)
- Connector Type: SC
- High-quality, machine-polished connectors with 100% end-face inspection that ensures consistent low-loss performance.

Ordering Information

Part Number	Description
119-01131	SC PIGTAIL 1M 50/125 MM OM3

Industry Standard

- RoHS, UL
- CE, ISO9001
- GR-326-CORE
- IEC 61300-3-35
- ISO/IEC 11801, IEC 24764
- TIA-568 C.0 / TIA-942
- Cenelec EN 50173-1
- Cenelec EN 50173-5

Applications

- Telecom, Data Centers and Transceiver connectivity

General Information

- Connector Polish Type: SC/UPC
- Sheath Material: PVC/LSZH
- Tight Buffer Color: Aqua
- Connector Color: Biege

PRODUCT TECHNICAL SPECIFICATION | SC PIGTAIL 50/125 MM OM3

Product Electrical Characteristics:

- Insertion loss: ≤ 0.20 dB
- Max. Insertion loss: ≤ 0.30 dB
- Repeatability: ≤ 0.10 dB
- Changeability: ≤ 0.20 dB
- Return loss: ≥ 30 dB (UPC), ≥ 35 dB (APC)

Sheath Physical Properties:

- Allowed Lateral Pressure: 100-1000 N/100mm
- Allowed Tensile Strength: 100-1000N
- Operation Temperature: -40°C to +75°C
- Storage Temperature: -40°C to +70°C

V3/1108/25