




LC PIGTAIL 9/125 SINGLE MODE

120-020XX

Phone
+33 75 864 2169

Email
info@angnetworks.com

Log 202, 5rue Albert Thomas, 38100
Grenoble, France.



Overview

- Fiber Type: Single Mode (9/125 um)
- Connector Type: LC
- High-quality, machine-polished connectors with 100% end-face inspection and compliance with GR-326-CORE that ensures consistent low-loss performance.

Ordering Information

Part Number	Description
120-02031	LC PIGTAIL 1M 9/125 SM
120-02033	LC PIGTAIL 2M 9/125 SM

Industry Standard

- RoHS, UL
- CE, ISO9001
- GR-326-CORE
- IEC 61300-3-35
- ISO/IEC 11801, TIA-568 B.3
- Cenelec EN 50173-1
- Cenelec EN 50173-5
- ITU-T G651

Applications

- Telecom, Data Centers and Transceiver connectivity

General Information

- Connector Polish Type: UPC
- Sheath Material: PVC/LSZH
- Tight Buffer Color: Yellow
- Connector Color: Blue

PRODUCT TECHNICAL SPECIFICATION | LC PIGTAIL 9/125 SINGLE MODE

Product Electrical Characteristics:

- Insertion loss: ≤ 0.20 dB
- Max. Insertion loss: ≤ 0.30 dB
- Repeatability: ≤ 0.10 dB
- Changeability: ≤ 0.20 dB
- Return loss: ≥ 40 dB (UPC)

Sheath Physical Properties:

- Allowed Lateral Pressure: 100-1000 N/100mm
- Allowed Tensile Strength: 100-1000N
- Operation Temperature: -40°C to $+75^{\circ}\text{C}$
- Storage Temperature: -40°C to $+70^{\circ}\text{C}$

V4/1603/26

HEADQUARTERS



A&G Technologies CO., Limited,
Log 202, 5rue Albert Thomas, 38100
Grenoble, France.

+33 75 864 2169

REGIONAL OFFICE



A&G Technologies (HK) CO., Limited,
Room 803, Chevalier House, 45-51 Chatham Road
South, Tsim Sha Tsui, Kowloon, Hong Kong.

+852 5420 8788

CONNECT THE FUTURE



info@angnetworks.com



www.angnetworks.com