

CAT 6 UTP KEYSTONE IDC

103-60011

Phone
+33 75 864 2169

Email
info@angnetworks.com

Log 202, 5rue Albert Thomas, 38100
Grenoble, France.



Overview

- RJ45 unshielded keystone Category 6 jack with 110/Krone punch-down style connector.
- Snap-in keystone jack is fast and easy to install
- Standard 110 IDC style termination allows for quick terminations

Industry Standard

- ISO/IEC11801, ISO/IEC 61156-5
- CENELEC EN 50173
- ANSI/TIA-568-C.2, EIA-310-D

Applications

- 1000BASE-TX Gigabit Ethernet
- 1000BASE-T Gigabit Ethernet
- 100BASE-TX Fast Ethernet
- 10BASE-T Ethernet
- Voice, Video, and other applications

Ordering Information

Part Number	Description
103-60011	CAT 6 KEYSTONE JACK IDC

PRODUCT TECHNICAL SPECIFICATION | CAT 6 UTP KEYSTONE IDC

Product Electrical Characteristics:

- Dielectric Strength: 1000V RMS for 1 minute
- Current Rating: 1.5 Amps Max.
- Insulation Resistance: 500MΩ Min.
- IDC Contact Resistance: 2.5mΩ max

Physical Properties:

- IDC Housing: Polycarbonate
- PCB Material: FR-4, UL94V-0
- Contact Material: Phosphor bronze with 50μ inch gold plating over nickel in contact area; 100μ inch nickel plated over phosphor bronze.
- Temperature Range: -10°C to 60°C
- Humidity: 10% to 90%; non-condensing
- Insertion Life: ≥750 mating cycles

V3/1209/25